



NSS Enterprises, Inc.

20" WALK-BEHIND SCRUBBERS

WRANGLER 2012 AB/DB

The Wrangler 2012 delivers high-productivity and cleaning performance you can count on. It is a perfect fit for hard floor cleaning programs found in retail, convenience stores, healthcare, schools, airports and hospitality.

- Durable and reliable. Built for tough commercial environments, the Wrangler 2012 will hold up year after year.
- Simplify operator training. The Wrangler 2012 has easy to understand controls, saving time when training new staff.
- Easy to maintain. The recovery tank on the Wrangler 2012 opens wide to allow thorough cleaning, helping to prevent foul odors from bacteria.
- Two models to fit any application:
 - Wrangler 2012 AB - A battery powered scrubber with a pad assisted drive.
 - Wrangler 2012 DB - A battery powered scrubber with a powered drive system to improve productivity.



DO NO HARM™

Stainless steel hardware, durable steel framework and heavy-duty rotomolded tanks keep the Wrangler 2012 on the job, and out of the landfill, for years.

Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

SPECIFICATIONS

WRANGLER 2012 AB/DB

Model	Wrangler 2012 AB	Wrangler 2012 DB
Cleaning Path	20 in (51 cm)	20 in (51 cm)
Brush/Pad	1 x 20 in	1 x 20 in
Solution Tank	12 gallons (45 L)	12 gallons (45 L)
Recovery Tank	14 gallons (53 L)	14 gallons (53 L)
Brush Motor (HP)	0.5 HP (380 W)	0.5 HP (380 W)
Brush Motor (RPM)	150	150
Pad Pressure (Lbs)	45, 80 (20, 36 kg)	45, 80 (20, 36 kg)
Vacuum Motor (HP)	0.5 HP (380 W)	0.5 HP (380 W)
Water Lift	46 in (116 cm)	46 in (116 cm)
Drive Motor (HP)	Not Applicable	0.34 HP (250 W)
Drive Wheel	2 x 8" (20 cm)	2 x 8" (20 cm)
Drive Speed (ft/min)	Not Applicable	Up to 250 ft/min (1.25 m/min)
Batteries, Quantity	2 x 12V	2 x 12V
Batteries, Size and Type	110 AH AGM 130 AH Wet	110 AH AGM 130 AH Wet
Run Time (Hours) 110 AH AGM 130 AH Wet	Up to 2.7 hours Up to 3.0 hours	Up to 2.7 hours Up to 3.0 hours
Sound Level (dBA)	62 dBA	62 dBA
Productivity (ft ² /hr) Theoretical Practical	14,960 (1,389 m ² /hr) 6,960 (646 m ² /hr)	20,000 (1,858 m ² /hr) 9,274 (681 m ² /hr)
Dimensions L x W x H (in) L x W x H (cm)	52 x 22 x 42 132 x 56 x 107	52 x 22 x 42 132 x 56 x 107
Weights Machine, 110 AH AGM Machine, 130 AH Wet Shipping, 110 AH AGM Shipping, 130 AH Wet	311 lbs (141 kg) 325 lbs (147 kg) 361 lbs (163 kg) 375 lbs (170 kg)	354 lbs (160 lbs) 368 lbs (166 kg) 404 lbs (183 kg) 418 lbs (189 kg)
Shipping Class	77.5	77.5
Warranty	3 years parts, 10 years on tanks	



1. A large basket in the recovery tank collects debris, preventing clogs in the drain hose.
2. The float shut-off protects the vacuum motor from liquid or foam damage.
3. The twist-grip handle easily controls forward and reverse motion.
4. A solenoid valve automatically shuts off the solution flow when the brush stops, preventing accidental spillage.
5. On-board battery charger recharges anywhere an outlet is available.
6. Extra tall drain hose allows draining into toilets and floor drains.
7. Main power key switch standard.
8. Two fill ports allow solution to be added from the front or the rear of the machine.
9. The clear solution tank hose indicates the amount of cleaning solution remaining and allows easy draining of the solution tank.
10. The 33-in squeegee swings wide on turns to leave the floor drier. The breakaway feature prevents damage if the squeegee catches on an object.



NSS ENTERPRISES, INC.

3115 Frenchmens Road
Toledo, OH 43607-2958
USA

(800) 677-1663 **TEL**
(419) 531-3761 **FAX**
info@nss.com

OPTIONS AND ACCESSORIES

ECOSTRIP



Ecostrip 400 pads are coated with a specially formulated diamond abrasive that can remove layers of floor finish without stripping chemicals.

NSS.COM